

## 2x2 PANEL LIGHT & COB DOWN LIGHT LINDA

### INDOOR LIGHT

COB LED downlight with die-cast aluminium housing in white powder coating finish, anti glare diffuser and separate energy efficient electronic driver.



#### Product features

- Aluminium Casting
- Available CCT : 3000 - 6500k
- Easy & fast Assembly
- Life Span : 50,000 Burning Hours
- LED : Bridgelux
- No UV Rays, No Mercury
- Energy Efficient

#### Driver Specifications

Input Voltage	: 110 - 240v AC	Power Factor	: >0.97
Frequency	: 50/60 Hz.	Thershold	: < 10%
Efficiency	: >93%		

#### Recommended Usage



Indoor Circulation areas



Hospital Area



Reception area



Retail Stores



Textile Industry

#### Technical Details



All Dimensions are in mm

Product Description	Code	Height	Overall Dimension	Cutout DIA
5w Linda COB DL	C 136	48	50	33
10w Linda COB DL	C 137	63	70	47
15w Linda COB DL	C 138	80	85	55
2X2 40w Slim PL	C 056	NA	600 X 600 SQ	595 X 595 SQ
2X2 40w Back lit PLt (Tri)	C 057	NA	600 X 600 SQ	595 X 595 SQ