

SUPERLITE PANEL **NX**(IN BUILT DRIVER) & **NX TRI-COLOR** (IN BUILT DRIVER) INDOOR LIGHT

New generation, environmental friendly, ultra modern shape Panel lighter with high brightness LEDs & polycarbonate Acrylic diffuser to give glare free soothing light effect, ideally suitable for Interiors.

Product features

- Aluminium Casting with Acrylic
- Available CCT : 3000 - 6500k
- Easy & fast Assembly
- Life Span : 50,000 Burning Hours
- LED : Bridgelux
- No UV Rays, No Mercury
- Energy Efficient

Driver Specifications

Input Voltage	: 110 - 240v AC	Power Factor	: >0.97
Frequency	: 50/60 Hz.	Threshold	: < 10%
Efficiency	: >93%		

Recommended Usage



Resturent area



Textile Industry



Indoor Circulation areas



Hospital Area



Retail Stores



Technical Details

All Dimensions are in mm



Color Temperature



Lumens



CRI



IP 20

Product Description	Code	Height	Overall Dimension	Cutout DIA
6w NX RPL/SQPL	C 159 R/S	20/26	121/121x121	102/105
12w NX RPL/SQPL	C 160 R/S	20/26	172/172x172	148/147
15w NX RPL/SQPL	C 161 R/S	20/26	172/172x172	148/147
18w NX RPL/SQPL	C 162 R/S	20/26	222/224x224	197/198
22w NX RPL/SQPL	C 163 R/S	20/26	222/224x224	197/198
6w NX TRI-COLOR RPL/SQPL	C 164 R/S	20/26	145/145x145	102/105
12w NX TRI-COLOR RPL/SQPL	C 165 R/S	20/26	172/172x172	148/147
15w NX TRI-COLOR RPL/SQPL	C 166 R/S	20/26	172/172x172	148/147
18w NX TRI-COLOR RPL/SQPL	C 167 R/S	20/26	222/224x224	197/198
22w NX TRI-COLOR RPL/SQPL	C 168 R/S	20/26	222/224x224	197/198