

SUPERLITE PANEL LIGHT & TRI-COLOR

INDOOR LIGHT

Ultra bright compact panel light with high brightness LED chips, ideally suited for low ceiling areas to give glare free light.

Product features

- Aluminium Casting with Acrylic
- Available CCT : 3000 - 6500k
- Easy & fast Assembly
- Life Span : 50,000 Burning Hours
- LED : Bridgelux

Driver Specifications

Input Voltage	: 110 - 240v AC	Power Factor	: >0.97
Frequency	: 50/60 Hz.	Thershold	: < 10%
Efficiency	: >93%		

Recommended Usage



Reception area



Retail Stores



Indoor Circulation areas



Hospital Area



Technical Details



Green/Blue/Red Available only in 3w

All Dimensions are in mm

Product Description	Code	Height	Overall Dimension	Cutout DIA
3w RPL/SQPL	C 005R/S	20/26	88/90x90	69/69
6w RPL/SQPL	C 006R/S	20/26	121/121x121	102/105
9w RPL/SQPL	C 007R/S	20/26	145/145x145	120/115
12w RPL/SQPL	C 008R/S	20/26	172/172x172	148/147
15w RPL/SQPL	C 009R/S	20/26	172/172x172	148/147
18w RPL/SQPL	C 010R/S	20/26	222/224x224	197/198
22w RPL/SQPL	C 011R/S	20/26	222/224x224	197/198
6w TRI-COLOR RPL/SQPL	C 017R/S	20/26	121/121x121	102/105
12w TRI-COLOR RPL/SQPL	C 018R/S	20/26	172/172x172	148/147
15w TRI-COLOR RPL/SQPL	C 019R/S	20/26	172/172x172	148/147
18w TRI-COLOR RPL/SQPL	C 020R/S	20/26	222/224x224	197/198