

NEW ADDED FEATURES BLUETOOTH, APP CONTROL, OFFLINE VOICE CONTROL

SUPERLITE **STYLO** PANEL LIGHT

INDOOR LIGHT

Ultraslim recess-mounting LED Panel light designed with new Technology

Product features

- Aluminium Casting with Acrylic
- Available CCT : 3000 - 6500k
- Easy & fast Assembly
- Life Span : 50,000 Burning Hours
- LED : Bridgelux
- No UV Rays, No Mercury
- Energy Efficient

Driver Specifications

Input Voltage	: 110 - 240v AC	Power Factor	: >0.97
Frequency	: 50/60 Hz.	Thershold	: < 10%
Efficiency	: >93%		

Recommended Usage



Indoor Circulation areas



Hospital Area



Reception area



Retail Stores



Textile Industry



Technical Details



All Dimensions are in mm

Product Description	Code	Height	Overall Dimension	Cutout DIA
15w STYLO (R) (1 Pcs) Without Remote	C 023R	26	172x172	147x147
15w STYLO (S) (1 Pcs) Without Remote	C 023S	20	172x172	147x147
15w STYLO (R) (4 Pcs) With 1 Remote	C 024R	20	172x172	147x147
15w STYLO (S) (4 Pcs) With 1 Remote	C 024S	26	172x172	147x147
15w STYLO COB (R) (1 Pcs) Without Remote	C 025R	NA	172x172	NA
15w STYLO SURFACE (R) ((1 Pcs) Without Remote	C 154R	NA	165x165	NA
15w STYLO SURFACE (S) (1 Pcs) Without Remote	C 154S	NA	165x165	NA
15w STYLO REMOTE ONLY	NA	NA	NA	NA