

# LED FLOOD LIGHT MARVEL & MARVEL PLUS

## OUTDOOR LIGHT

The long 50,000 hour rated life significantly decreases maintenance labour and material costs over the life of the fixture.

### Product features

- Aluminium Casting with Toughend Glass
- Available CCT 3000 - 6500k
- Easy & fast Assembly
- Life Span of 50,000 Burning Hours
- LED : Bridgelux
- No UV Rays, No Mercury, No Infrared
- Energy Efficient

### Driver Specifications

Input Voltage	: 110 - 240v AC	Power Factor	: >0.97
Frequency	: 50/60 Hz.	Thershold	: < 10%
Efficiency	: >93%		

### Recommended Usage



Breather

### Technical Details

All Dimensions are in mm



Color Temperature



Lumens



CRI



IP 65

Product Description	Code	Length	Height	Width
30W Marvel Flood Light	C 084	250	130	185
60W Marvel Flood Light	C 085	315	150	235
45W Marvel Plus Flood Light	C 086	250	130	185
60w Marvel Plus Flood Light	C 087	250	130	185
80w Marvel Plus Flood Light	C 088	315	105	235
100w Marvel Plus Flood Light	C 089	315	105	235
100W Marvel Flood Light	C 090	340	105	224
120W Marvel Flood Light	C 091	315	105	235
150W Marvel Flood Light	C 092	370	110	290
250W Marvel Flood Light	C 093	670	195	320
400W Marvel Flood Light	C 094	670	195	320

