

HIGHBAY LIGHTS ZIBE & SUPER Highbay, MINI Highbay, WELLGLASS FITTING

INDOOR LIGHT

Significantly reduce electricity usage, Decreases monthly power costs,
Markedly improve lighting quality, Provide a safer and more productive work environment.

Product features

- Aluminium Casting with Toughend Glass
- Aluminium Casting with Acrylic LENS (ZIBE)
- Aluminium Casting with WELLGLASS
- Available CCT 3000 - 6500k
- Easy & fast Assembly
- Life Span of 50,000 Burning Hours
- LED : Bridgelux
- No UV Rays, No Mercury, No Infrared
- Energy Efficient

Driver Specifications

Input Voltage : 110 - 240v AC	Power Factor : >0.97
Frequency : 50/60 Hz.	Thershold : < 10%
Efficiency : >93%	

Recommended Usage



Factories

Auditorium

Godowns

Airports

Technical Details

All Dimensions are in mm



Color Temperature

Lumens

CRI

IP 20

Product Description	Code	Length	Height	Reflector Dia
100w Zibe Hibay (Lens Model)	C 099	250	150	NA
150w Zibe Hibay (Lens Model)	C 100	295	140	NA
200w Zibe Hibay (Lens Model)	C 131	350	120	NA
100w Super Hibay	C 101	380	240	485
150w Super Hibay	C 102	380	240	485
200w Super Hibay	C 103	425	280	540
250w Super Hibay	C 104	425	280	540
300w Super Hibay	C 105	425	280	540
50w Mini Hibay	C 134	175	100	NA
50w Well Glass(Milky/Clear)	C 135M/C	175	170	NA



• SUPER Highbay

• ZIBE

• MINI Highbay

• WELL GLASS